

	De	claration of Performance	
	(model in accordance with deleg	gated regulation Nr. 574/2014 of the	e European Commission)
		nr BRD008	
1.	Unique identification code of	FOLIEFOL TOP, nr BRD008	
	product-type		
2.	Intended use/uses	Reinforced elastic sheets for the application of underlayer for	
		discontinuous roofing (and siding of the façade)	
3.	Manufacturer	Berdal Rubber & Plastics BV	
		Bedrijvenpark Twente 193	
		7602 KG Almelo – The Netherlands	
4.	Authorised representative	Not applicable	
5.	The system or systems for	AVCP 3	
	assesssing and verifying		
	performance resistance (AVCP)	^ ^ /	
6a.	Harmonised standard	EN 13984-2	
	Notified outbority	Contrum Staughnike interventuies a patification no. 1200	
	Notified authority	Centrum Stavebniho inzenyrstvi a.s., notification no.: 1390	
7.	Declared performance (s)	Essential features:	Performances:
		Fire reaction	Classe F
		Impermeability	Conform NEN-EN 13984
		Water vapour transmission rate	25
		(Sd)	35 m
		Impact load resistance	NPD (no Performance
			Determined)
		Adhesion strength	NPD
		Ultimate tensile strength	>210/>190 N/50 mm)
		MD/CMD	
		Tear resistance MD/CMD	>135/>125 N
		Resistance to alkali	NPD (No Performance Determined
	7	Durability with regard to water	Conform EN 1296 en EN 1931
		vapour permeability by ageing	

The performance of the product identified is in comformity with the set of declared performance/s. This declaration of performance is issued in accordance with (EU) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer.

B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018