

Bedrijvenpark Twente 193 NL-702 KG Almelo – The Netherlands

Tel : +31 (0)546 - 572 672 Mail: info@berdal.com

	De	claration of Performance	
	(model in accordance with dele	gated regulation Nr. 574/2014 of the	European Commission)
		Nr BRD023	
1.	Unique identification code of product-type	Foliefol DPC, Nr BRD023	
2.	Intended use/uses	DPC film for the connection of window frames in facades.	
3.	Manufacturer	Berdal Rubber & Plastics BV Bedrijvenpark Twente 193 7602 KG Almelo – The Netherlands	
4.	Authorised representative	Not applicable	
5.	The system or systems for assesssing and verifying performance resistance (AVCP)	AVCP 3	
6a.	Harmonised standard	EN 14909	
	Notified authority	Instytut techniki budowlanej (ITB), notification nr. 1488	
7.	Declared performance (s)	Essential features:	Performances:
		Thickness	0.3 ± 10%
		Tensile Strength	16,3 Mpa (longitudinal direction) 16.0 Mpa (cross direction)
		Relative elongation at maximum strength	578 (longitudinal direction) 649 (cross direction)
		Static performance resistance	20 kg
		Resistance to impact	≥ 200 mm
		Resistance to low temperature	-25°C
		Water resistance in artificial ageing	'Pass'at 2 kPa

The performance of the product identified is in comformity with the set of declared performance/s. This declaration of performance is issued in accordance with (UE) No 305/2011, under the sole responsibility of manufacturer identified above.

Signed for and on behalf of the manufacturer.

B.M.D. van Kamperdijk, General Manager

Almelo, The Netherlands, 1 March 2018